


**Gelato - Ice cream - G111ce-Eis - Hel11do****BTMD10**Carrello su richiesta  
Trolley on requestConservatore di gelato a  
varie combinazioni

divaschette.

Ice cream preserver  
with various basins  
combination.**Produzione oraria L**Hourly production L - Production Horaire L  
Produktion pro Stunden L - Producción /hora L

III

**Minima quantità liquida per ciclo introdotta (L)/(kg)**

Min liquid quantity per batch introduced (L)/(kg)

Quantite min. de liquide par cycle (L)/(kg)

Min. Flüssigkeitsmenge pro Zyklus eingeführt (L)/(kg)

Cantidad líquida mínima por la hornada introducida (U)/(kg)

1/1,150

**Massima quantità liquida per ciclo introdotta (L)/(kg)**

Max liquid quantity per batch introduced (L)/(kg)

Quantite max. de liquide par cycle (U)/(kg)

Max. Flüssigkeitsmenge pro Zyklus eingeführt (L)/(kg)

2/2.3

**Voltaggio standard**

Standard Voltage - Tension Standard

230V 50Hz

Standardspannung - Standard Voltajes

**Potenza W**

Power W - Puissance W

1150

Leistung W - Potencia W

**Dimensioni nette mm BTMD10 V**

Net dimensions mm - Dimensions net mm

870x710x599+24

Nettoabmessungen mm - Dimensiones neto mm

**Dimensioni nette mm BTMD10 C**

Net dimensions mm - Dimensions net mm

570x710x571+24

Nettoabmessungen mm - Dimensiones neto mm

**Peso netto kg**

Net weight kg - Poids net kg

65

Nettogewicht kg - Peso neto kg

**Dimensioni lorde (Lx.PxA) mm**

Gross dimensions (WxDxH) mm

920x710x800

Dimensions brutes (LxPxH) mm

Bruttoabmessungen (BxTxH) mm

Dimensiones brutas (LxPxA) mm

**Peso lordo kg**

Gross weight kg - Poid brut kg

kg70

Bruttogewicht kg - Peso bruto kg

Vol.m<sup>3</sup>0.53**Capacità vaschette BTMD10V**

Basins capacity - Capacite bassins

n°4 x 2,5 l

n°2 x 5L

n°2 x 2.5 L+ n°1x 5 L

**Capacità carapine BTMD10 C**

Tubs capacity - Capacite bassins

n°4 x 2,2 L

Kapazität Becken - Capacidad cubetas



BTMD10 V



BTMD10 C

**Gelato - Ice cream - Glace-Eis - Helado****BTM10  
+10**Carrello su richiesta  
Trolley on request**Produzione oraria L**Hourly production L - Production Horaire L  
Produktion pro Stunden L - Producción /hora L

20

**Minima quantità liquida per ciclo introdotta (L)/(kg)**

Min liquid quantity per batch introduced (L)/(kg)

Quantite min. de liquide par cycle (L)/(kg)

Min. Flüssigkeitsmenge pro Zyklus eingeführt (L)/(kg)

Cantidad líquida mínima por la hornada introducida (U)/(kg)

1/1,150

**Massima quantità liquida per ciclo introdotta (L)/(kg)**

Max liquid quantity per batch introduced (L)/(kg)

Quantite max. de liquide par cycle (L)/(kg)

Max. Flüssigkeitsmenge pro Zyklus eingeführt (L)/(kg)

4/4,6

**Voltaggio standard**

Standard Voltage - Tension Standard

230V 50Hz

Standardspannung - Standard Voltajes

**Potenza W**

Power W - Puissance W

2200

Leistung W - Potencia W

**Dimensioni nette mm**

Net dimensions mm - Dimensions net mm

870x710x491+24

Nettoabmessungen mm - Dimensiones neto mm

**Peso netto kg**

Net weight kg - Poids net kg

85

Nettogewicht kg - Peso neto kg

**Dimensioni lorde (Lx.PxA) mm**

Gross dimensions (WxDxH) mm

920x710x800

Dimensions brutes (LxPxH) mm

Bruttoabmessungen (BxTxH) mm

Dimensiones brutas (LxPxA) mm

**Peso lordo kg**

Gross weight kg - Poid brut kg

kg105 Vol.m<sup>3</sup>0,53

Bruttogewicht kg - Peso bruto kg

**GROUPE  
PROTEC  
INC.**9601, rue Colbert, Anjou, Qc H1J-1Z9  
Tél : 514-725-4040 fax : 514-789-2778

www.groupeprotec.com info@groupeprotec.com