





EQUIPEMENT

	Modèle	Description			
CASES					
		<ul style="list-style-type: none"> - <u>OPEN MERCHANDISERS</u> - Forced air system - Interior lighting - Adjustable shelves - Digital temperature control - Automatic defrosting - Night curtain included - Temperature +1C° to +4C° • The equipment is designed to operate under normal environmental conditions being below 75°F / 24°C ambient, 55% Relative Humidity. 			
	R10 4'	48" (W) X 36" (D) X 80" (H)	220V, 60HZ, 15amps		
	R14 4.5'	56" (W) X 36" (D) X 80" (H)	220V, 60HZ, 15amps		
	R16 5'	64" (W) X 36" (D) X 80" (H)	220V, 60HZ, 15amps		
	R18 6'	72" (W) X 36" (D) X 80" (H)	220V, 60HZ, 20amps		
	R20 6.5'	80" (W) X 36" (D) X 80" (H)	220V, 60HZ, 20amps		
	R25 8.5'	104" (W) X 36" (D) X 80" (H)	220V, 60HZ, 20amps		


	Modèle	Description			
MULTI USE CASE C-GY					
		<p>Standard:</p> <ul style="list-style-type: none"> • Curved front glass flip open for easy cleaning • Tempered front glass • Mirror finish interior with SS floor • Two SS adjustable and removable shelves • ABS gray sides • Automatic defrosting • Automatic condensation disposal • Interior LED lighting • Self-closing double glass doors • Front window defogger • Environment friendly R 134A • The equipment is designed to operate under normal environmental conditions being below 75°F / 24°C ambient, 55% Relative Humidity. 			
	C12GT 4'	48" (W) X 34" (D) X 46" (H)	115V, 60HZ, 8amps		
	C18GT 6'	72" (W) X 34" (D) X 46" (H)	115V, 60HZ, 10amps		
	C24GT 8'	96" (W) X 34" (D) X 46" (H)	115V, 60HZ, 15amps		


EQUIPEMENT

	Modèle	Description		
MULTI USE CASE C-GY				
	<p>Standard:</p> <ul style="list-style-type: none"> • Curved front glass ; • Mirror finish interior with SS floor ; • Granite work top (width 30mm) ; • Stainless steel pull out display drawer; • Two leveled interior lighting ; • Temperature control with thermometer ; • ABS sides ; • Automatic defrosting ; • Side gravity coil ; • Front window defogger ; • Environment friendly R 507 ; • The equipment is designed to operate under normal environmental conditions being below 75°F / 24°C ambient, 55% Relative Humidity. 			
	C-12G	48" (W) X 37" (D) X 55" (H)	115V, 60HZ, 8 amps	
	C-14G	56" (W) X 37" (D) X 55" (H)	115V, 60HZ, 8 amps	
	C-16G	64" (W) X 37" (D) X 55" (H)	115V, 60HZ, 8 amps	
	C-20G	80" (W) X 37" (D) X 55" (H)	115V, 60HZ, 8 amps	

	Modèle	Description		
EUROPEAN PASTRY CASE				
	<p>Standard:</p> <ul style="list-style-type: none"> • Forced air refrigeration system ; • Curved front glass ; • Mirror finish interior with SS floor ; • S/S work top (width 30 mm); • Four levelled interior lighting; • Temperature control with thermometer ; • ABS sides ; • Automatic defrosting ; • Front window defogger ; • Environment friendly R 507; • The equipment is designed to operate under normal environmental conditions being below 75°F / 24°C ambient, 55% Relative Humidity. 			
	C-09 GN 3.2'	37" (W) X 37" (D) X 54" (H)	115V, 60HZ, 8amps	1/3 HP
	C-13 GN 4.5'	53" (W) X 37" (D) X 54" (H)	115V, 60HZ, 10amps	1/3 HP
	C-17 GN 5.9'	69" (W) X 37" (D) X 54" (H)	115V, 60HZ, 10amps	1/2 HP

EQUIPEMENT

	Modèle	Description	capacité	
DELI, CHEESE, FRESH MEAT, FISH AND SALADS				
	<ul style="list-style-type: none"> • Curved front glass; • Mirror finish interior with SS floor ; • Granite back counter; • ABS sides ; • Interior lighting ; • Temperature control with thermometer ; • Automatic defrosting; • Gravity coil system ; • Front window defogger ; • Double Duty complete with refrigerated bottom storage; • S/S bottom panel ; • Environment friendly R 507 ; • The equipment is designed to operate under normal environmental ; <p>conditions being below 75°F / 24°C ambient, 55% Relative Humidity.</p>			
	CONVEX CORNER	W-12 SGSN 4'	50" L X 43" D X 50" H	115V, 60HZ, 8 amps
	W-18 SGSN 6'	74" L X 43" D X 50" H	115V, 60HZ, 16 amps	1/2 HP
	W-24 SGSN 8'	96" L X 43" D X 50" H	115V, 60HZ, 16 amps	2 X 1/3 HP
	W-30 SGSN 10'	120" L X 43" D X 50" H	115V, 60HZ, 16 amps	2 X 1/2 HP
CONCAVE CORNER	W-12 SGS NZ	96" L X 43" D X 50" H	115V, 60HZ, 8 amps	1/3 HP
	W-12 SGS NW	98" L X 43" D X 50" H	115V, 60HZ, 8 amps	1/3 HP

	Modèle	Description		
DELI, CHEESE, FRESH MEAT, FISH AND SALADS				
	<p>Standard:</p> <ul style="list-style-type: none"> • Curved front glass ; • Mirror finish interior with SS floor ; • Granit back counter; • ABS gray sides ; • Interior lighting ; • Temperature control with thermometer; • Automatic defrosting ; • Gravity coil system ; • Front window defogger ; • Double Duty complete with refrigerated bottom storage; • Environment friendly R 507 • The equipment is designed to operate under normal environmental conditions being below 75°F / 24°C ambient, 55% Relative Humidity. 			
	CONVEX CORNER	W-12NG 4'	50 " (W) X 46" (D) X 50 "	115V, 60HZ, 8amps
	W-18NG 6'	74" (W) X 46" (D) X 50 "	115V, 60HZ, 16 amps	1/2 HP
	W-24NG 8'	96 " (W) X 46" (D) X 50 "	115V, 60HZ, 16 amps	2 X 1/3 HP
	W-30NG 10'	120 " (W) X 46" (D) X 50"	115V, 60HZ, 16 amps	2 X 1/2 HP
CONCAVE CORNER	W-12NG NZ	96" (W) X 46" (D) X 50 "	115V, 60HZ, 8amps	1/3 HP
	W-12NG NW	98" (W) X 46" (D) X 50 "	115V, 60HZ, 8amps	1/3 HP