



Model:
MUC--36R

Undercounter:
Solid Door Refrigerator



- ▶ True's undercounter units are designed with enduring quality that protects your long term investment.
- ▶ Designed using the highest quality materials and components to provide the user with colder product temperatures, lower utility costs, exceptional food safety and the best value in today's food service marketplace.
- ▶ Oversized, environmentally friendly (134A) forced-air refrigeration system holds 33°F to 38°F (.5°C to 3.3°C).
- ▶ All stainless steel front, top and cabinet ends. Matching aluminum finished back.
- ▶ Front breathing.
- ▶ Foamed-in-place, high density polyurethane insulation (CFC free).
- ▶ Heavy duty PVC coated wire shelves.

ROUGH-IN DATA

Specifications subject to change without notice.
Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

| Model | Solid Doors | Capacity (Cu. Ft.) (liters) | # of Shelves | Cabinet Dimensions (inches) (mm) | | | HP | Voltage | Amps | NEMA Config. | Cord Length (total ft.) (total m) | Crated Weight (lbs.) (kg) |
|---------|-------------|-----------------------------|--------------|---------------------------------------|---------------------------------------|---------------------------------------|------------|--------------------------|------------|--------------|-----------------------------------|---------------------------|
| | | | | L | D† | H* | | | | | | |
| MUC-36R | 2 | 8.5 241 | 4 | 36 ³ / ₈ 924 | 30 ¹ / ₈ 766 | 29 ³ / ₄ 756 | 1/3 1/3 | 115/60/1 230-240/50/1 | 8.3 4.2 | 5-15P ▲ | 7 2.13 | 225 103 |

* Depth does not include 1" (26 mm) for rear bumpers.

▲ Plug type varies by country.

† Height does not include 6¹/₄" (159 mm) for castors or 6" (153 mm) for optional legs.



APPROVALS: