

Display Case

Plane Glass Refrigerated Cold Deli Case

- Balanced refrigeration system designed to operate at 36°F~43°F.
- Stainless steel floor and walls, standard.
- Sliding doors.
- 12V LED lighting system, safe for users to operate.
- Adjustable glass shelves provide extra large viewing area to maximize bakery product presentation.
- NSF-7 compliant for open food product.
- Tempered glass to avoid injury by broken glass.
- Hidden caster design.
- Easily accessible condenser coil for cleaning, and easy service access.



Model	PCV2-36	PCV2-48	PCV2-60	PCV2-72
Doors	2	2	2	2
Temperature range	36°F~43°F (2°C~6°C)	36°F~43°F (2°C~6°C)	36°F~43°F (2°C~6°C)	36°F~43°F (2°C~6°C)
Capacity	11.3 (cu.ft.) / 320 (L)	14 (cu.ft.) / 400 (L)	17.7 (cu.ft.) / 500 (L)	21.2 (cu.ft.) / 600 (L)
Shelves	2 Layers	2 Layers	2 Layers	2 Layers
External dimensions (L x W x H)	35 3/8 x 28 3/4 x 47 1/4 (in) 900x730x1200 (mm)	47 1/4 x 28 3/4 x 47 1/4 (in) 1200x730x1200 (mm)	59 1/8 x 28 3/4 x 47 1/4 (in) 1500x730x1200 (mm)	70 7/8 x 28 3/4 x 47 1/4 (in) 1800x730x1200 (mm)
Compressor HP	1/3+	1/3+	1/2+	1/2+
Voltage	115V/60Hz 220~240/50Hz	115V/60Hz 220~240/50Hz	115V/60Hz 220~240/50Hz	115V/60Hz 220~240/50Hz
NEMA Config	5-15P	5-15P	5-15P	5-15P

*Plug type varies by country



Model	PCV3-36	PCV3-48	PCV3-60	PCV3-72
Doors	2	2	2	2
Temperature range	36°F~43°F (2°C~6°C)	36°F~43°F (2°C~6°C)	36°F~43°F (2°C~6°C)	36°F~43°F (2°C~6°C)
Capacity	12.7 (cu.ft.) / 360 (L)	19.4 (cu.ft.) / 550 (L)	25 (cu.ft.) / 700 (L)	30 (cu.ft.) / 850 (L)
Shelves	3 Layers	3 Layers	3 Layers	3 Layers
External dimensions (L x W x H)	35 3/8 x 28 3/4 x 55 1/8 (in) 900x730x1400 (mm)	47 1/4 x 28 3/4 x 55 1/8 (in) 1200x730x1400 (mm)	59 1/8 x 28 3/4 x 55 1/8 (in) 1500x730x1400 (mm)	70 7/8 x 28 3/4 x 55 1/8 (in) 1800x730x1400 (mm)
Compressor HP	1/3+	1/3+	1/2+	1/2+
Voltage	115V/60Hz 220~240/50Hz	115V/60Hz 220~240/50Hz	115V/60Hz 220~240/50Hz	115V/60Hz 220~240/50Hz
NEMA Config	5-15P	5-15P	5-15P	5-15P

*Plug type varies by country