

Model:

CFD-Series:

SDRIFX-53 Reach-In Solid Swing Door Freezer



- **Stainless steel interior and exterior** retains attractive finish longer.
- **Rounded corner** design inside of the cabinet makes it easy to clean the inside storage room
- **Standard door features:**
Heavy-duty pull handle
Each door with two spring hinges, this make the door self-closing with enduring quality
- **Refrigeration system** holds -8°F to 0°F (-22°C to -18°C) for the best in food preservation.
- **Electronic control system:**
Adjustable temperature set point and defrost frequency
Error codes to diagnose service issues
- **Shelf:** Adjustable, heavy duty PVC coated shelves.
- **Standard heavy-duty casters** make it easy to move and clean underneath


Bottom mounted units feature:

- "No stoop" lower shelf.
- Storage on top of cabinet.
- Easily accessible condenser coil for cleaning, and easy service access
- Simple installation with no plumbing required

Rough-In Data

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

Model	Doors	Shelves	Cabinet Dimensions (inches / mm)			CAP. CU.FT. LITER	HP	Voltage	Amps	NEMA Config. 5-20P 
			L	D	H					
SDRIFX-53	3	9	80.9 2054	32.2 818	82.5 2095	72 2040	1	115/60/1	14	30 amps Circuit Breaker is recommended to be connected to the plug base directly

Plug type varies by country.

