

MAT Series

REFRIGERATED DISPLAY



MODELS | MATSLS4 / MATSLS6

MAT SERIES – REFRIGERATED DISPLAY

Enhance the presentation of your cold food items.

CABINET CONSTRUCTION

Heavy duty construction includes stainless steel body base with a double tempered glass top.

REFRIGERATION SYSTEM

Environmentally safe R134A refrigerant. Back side condensing unit positioned for easy maintenance.

Maintains a temperature range from 2°C to 10°C. Includes automatic defrost setting with a ventilated cooling system.

STORAGE

2 spaces of storage (grab n go and serve over)

SPECIAL FEATURES

- Brilliant internal LED illumination
- Digital temperature control
- Adjustable glass shelves
- Double tempered glass
- Ventilated cooling system
- Automatic defrost




TECHNICAL DATA

MODEL	WEIGHT N.W (KG) G.W (KG)	TEMPERATURE	REFRIGERANT	DIMENSIONS-WxDxH Inches mm	CAPACITY L FT ³	AMPS	VOLTAGE
MATSLS4	280 320	2°C to 10°C	R134A	47 ¼ X 39 ½ X 59 1200 X 1003 X 1499	500 17.66	10.1	115V
MATSLS6	380 420	2°C to 10°C	R134A	70 ¾ X 39 ½ X 59 1797 X 1003 X 1499	700 24.72	17.9	115

NOTE : These merchandisers are designed for use in stores when temperature and humidity do not exceed 24°C and 55% RH. Designed for holding pre-chilled product only.

We reserve the right to change or revise specifications and product design in connection with any feature of our products. Such changes do not entitle the buyer to corresponding changes, improvements, additions, or replacements for equipment previously sold or shipped.



NEMA 5-15P