




REFRIGERATED DISPLAY – 3 SHELVES

- LED light in illumination
- Accurate digital controller, the LED display shows the precise working temperature.
- High quality imported compressor, energy saving and low noise.
- Baked castors for easy moving
- Top-mounted door track with high quality imported bearing, low noise and smooth.
- Whole unit of cooling system and electronic board can be taken out. Easy for cleaning and maintaining
- Forced air cooling system ensures effective air circulation
- Automatic defrost ensures the evaporator working to its optimum performance
- Automatic vaporizing the defrosted water.



Building
superior
quality

MATGL860P

MODEL	WEIGHT N.W (KG) G.W (KG)	TEMPERATURE	REFRIGERANT	DIMENSIONS – WxDxH Inches mm	CAPACITY L FT ³	AMPS	VOLTAGE	PLUG TYPE
MATGL840P	324 379	2 °C to 8 °C	R134A	70 ¾ X 29 ½ X 53 ¼ 1800 X 800 X 1370	785 27.72	5.5	115 60Hz	NEMA 5-15P 



NOTE : These merchandisers are designed for use in stores when temperature and humidity do not exceed 24 °C and 55% RH. Designed for holding pre-chilled product only.

We reserve the right to change or revise specifications and product design in connection with any feature of our products. Such changes do not entitle the buyer to corresponding changes, improvements, additions, or replacements for equipment previously sold or shipped.