



UNDERCOUNTER REFRIGERATOR – 1,2 OR 3 DOORS

- Stainless steel interior and exterior, aluminum back. Option of bright white aluminum interior available
- Refrigeration system keeps food at safe temperatures between 0.5°C to 5 °C
- Self-closing doors with 90 degree stay-open feature
- Shelves : adjustable heavy-duty PVC coated shelves
- Option of backsplashes available
- Electronic control system makes it easy to adjust temperature set point and defrost frequency
- Preinstalled heavy-duty casters with brakes
- Removable installation board makes it easy to access condenser coil for cleaning and service
- Option of different handles available

Building superior quality



MUC27R



MUC48R - MUC60R



MUC72R

MODEL	DOORS	SHELVES	WEIGHT N.W (KG) G.W (KG)	TEMPERATURE	REFRIGERANT	DIMENSIONS – WxDxH Inches mm	CAPACITY L FT ³	AMPS	VOLTAGE	PLUG TYPE
MUC27R	1	1		0.5°C to 5°C	R290	27 x 29 1/2 x 35 1/5 685 x 750 x 895	177 6.3	1.9	115 60Hz	NEMA 5-15P
MUC48R	2	2		0.5°C to 5°C	R290	47 1/5 x 29 1/2 x 35 1/5 1200 x 750 x 895	338 12	2.7	115 60Hz	NEMA 5-15P
MUC60R	2	2		0.5°C to 5°C	R290	60 1/5 X 29 1/2 X 35 1/5 1526 X 750 X 895	428 15	2.9	115 60Hz	NEMA 5-15P
MUC72R	3	3		0.5°C to 5°C	R290	72 X 29 1/2 X 35 1/5 1829 X 750 X 895	440 15.5	3.2	115 60Hz	NEMA 5-15P

NOTE : These merchandisers are designed for use in stores when temperature and humidity do not exceed 24 °C and 55% RH. Designed for holding pre-chilled product only.

We reserve the right to change or revise specifications and product design in connection with any feature of our products. Such changes do not entitle the buyer to corresponding changes, improvements, additions, or replacements for equipment previously sold or shipped.



Intertek Intertek