



REFRIGERATED DISPLAY – 2 SHELVES

- **Refrigeration system** maintains temperatures between 2 °C to 6 °C
- **Exterior** : Stainless steel floor and walls, standard
- **Sliding doors**
- **12 V LED lighting** system, safe for users to operate
- **Tempered glass** to avoid injury by broken glass
- Preinstalled hidden caster design
- **Shelves** : Adjustable glass shelves provide extra large viewing area to maximize bakery product presentation
- **Electronic control system** makes it easy to adjust temperature set point and defrost frequency
- Removable installation board makes it easy to access condenser coil for cleaning and service
- **NSF-7** compliant for open food product

Building superior quality



PCV2-36

PCV2-48

PCV2-60

PCV2-72

MODEL	WEIGHT N.W (KG) G.W (KG)	TEMPERATURE	REFRIGERANT	DIMENSIONS – WxDxH Inches mm	CAPACITY L FT ³	AMPS	VOLTAGE	PLUG TYPE
PCV2-36	168 188	2 – 6 °C	R290	35 3/8 X 28 3/4 X 47 1/4 900 x 730 x 1200	320 11.3	6.9	115 60Hz	NEMA 5-15P
PCV2-48	210 230	2 – 6 °C	R290	47 1/4 X 28 3/4 X 47 1/4 1200 X 730 X 1200	400 12	7.2	115 60Hz	NEMA 5-15P
PCV2-60	250 270	2 – 6 °C	R290	59 1/8 X 28 3/4 X 47 1/4 1500 X 730 X 1200	500 17.7	8.1	115 60Hz	NEMA 5-15P
PCV2-72	285 305	2 – 6 °C	R290	70 7/8 X 28 3/4 X 47 1/4 1800 X 730 X 1200	600 21.2	8.3	115 60Hz	NEMA 5-15P

NOTE : These merchandisers are designed for use in stores when temperature and humidity do not exceed 24 °C and 55% RH. Designed for holding pre-chilled product only.

We reserve the right to change or revise specifications and product design in connection with any feature of our products. Such changes do not entitle the buyer to corresponding changes, improvements, additions, or replacements for equipment previously sold or shipped.



Intertek Intertek