



## REFRIGERATED DISPLAY – 3 SHELVES

- **Refrigeration system** maintains temperatures between 2 °C to 6 °C
- **Exterior** : Stainless steel floor and walls, standard
- **Sliding doors**
- **12 V LED lighting** system, safe for users to operate
- **Tempered glass** to avoid injury by broken glass
- Preinstalled hidden caster design
- **Shelves** : Adjustable glass shelves provide extra large viewing area to maximize bakery product presentation
- **Electronic control system** makes it easy to adjust temperature set point and defrost frequency
- Removable installation board makes it easy to access condenser coil for cleaning and service
- **NSF-7** compliant for open food product

Building superior quality



PCV3-36



PCV3-48



PCV3-60



PCV3-72

MODEL	WEIGHT N.W (KG) G.W (KG)	TEMPERATURE	REFRIGERANT	DIMENSIONS – WxDxH Inches mm	CAPACITY L FT <sup>3</sup>	AMPS	VOLTAGE	PLUG TYPE
PCV3-36	190 210	2 – 6 °C	R290	35 3/8 X 28 3/4 X 55 1/8 900 x 730 x 1400	360 12.7	7.3	115 60Hz	NEMA 5-15P 
PCV3-48	238 258	2 – 6 °C	R290	47 1/4 X 28 3/4 X 55 1/8 1200 X 730 X 1400	550 19.4	7.5	115 60Hz	NEMA 5-15P 
PCV3-60	276 296	2 – 6 °C	R290	59 1/8 X 28 3/4 X 55 1/8 1500 X 730 X 1400	700 25	8.3	115 60Hz	NEMA 5-15P 
PCV3-72	320 340	2 – 6 °C	R290	70 7/8 X 28 3/4 X 55 1/8 1800 X 730 X 1400	850 30	8.5	115 60Hz	NEMA 5-15P 



**NOTE** : These merchandisers are designed for use in stores when temperature and humidity do not exceed 24 °C and 55% RH. Designed for holding pre-chilled product only.

We reserve the right to change or revise specifications and product design in connection with any feature of our products. Such changes do not entitle the buyer to corresponding changes, improvements, additions, or replacements for equipment previously sold or shipped.