



## REFRIGERATED PREPARATION TABLE – 1 OR 2 DOORS

- Stainless steel interior and exterior, aluminum back. Option of bright white aluminum interior available
- Refrigeration system keeps food at safe temperatures between 0.5°C to 5°C
- Self-closing doors with 90 degree stay-open feature
- Shelves : adjustable heavy-duty PVC coated shelves
- Cutting boards and pans available
- Electronic control system makes it easy to adjust temperature set point and defrost frequency
- Preinstalled heavy-duty casters with brakes
- Removable installation board makes it easy to access condenser coil for cleaning and service
- Option of different handles available

Building superior quality



PT-1-27



PT-2-48

MODEL	DOORS	SHELVES	WEIGHT N.W (KG) G.W (KG)	TEMPERATURE	REFRIGERANT	DIMENSIONS – WxDxH Inches mm	CAPACITY L FT <sup>3</sup>	AMPS	VOLTAGE	PLUG TYPE
PT-1-27	1	1		0.5°C to 5°C	R290	27 1/2 x 29 1/2 x 42 3/8 698 x 750 x 1075	160 5.7	2.88	115 60Hz	NEMA 5-15P 
PT-2-48	2	2		0.5°C to 5°C	R290	46 7/8 x 29 1/2 x 42 3/8 1188 x 750 x 1075	268 9.5	4.56	115 60Hz	NEMA 5-15P 



**NOTE :** These merchandisers are designed for use in stores when temperature and humidity do not exceed 24 °C and 55% RH. Designed for holding pre-chilled product only.

We reserve the right to change or revise specifications and product design in connection with any feature of our products. Such changes do not entitle the buyer to corresponding changes, improvements, additions, or replacements for equipment previously sold or shipped.